


PRODUCT-DETAILS

## SA/S12.6.2.2

### SA/S12.6.2.2 Switch Actuator, 12-fold, 6 A, MDRC



#### Informations générales

|                              |   |
|------------------------------|---|
| Extension du type de produit | SA/S12.6.2.2  |
| Code de produit              | 2CDG110256R0011   |
| EAN                          | 4016779066778   |
| Description courte           | SA/S12.6.2.2 Switch Actuator, 12-fold, 6 A, MDRC  |
| Description longue           | The switch actuator uses potential free contacts to switch 12 independent electrical loads via the ABB i-bus® KNX. The device features a manual operation and displaying of the switching state of the outputs. The 6 A device is especially suited to switch resistive, inductive or capacitive loads. The device is powered by KNX and requires no additional power supply. |

#### Commande

|                        |               |
|------------------------|---------------|
| EAN                    | 4016779066778 |
| Code douanier          | 85371091      |
| Quantité minimum       | 1 pièce       |
| E-Number (Switzerland) | 405 660 125   |
| E-Number (Finland)     | 2814691       |
| E-Number (Sweden)      | 1739894       |

#### Dimensions

|                      |         |
|----------------------|---------|
| Produit Longueur Net | 63.5 mm |
| Produit Hauteur Net  | 90 mm   |
| Produit Largeur Net  | 210 mm  |

|           |          |
|-----------|----------|
| Poids net | 0.608 kg |
|-----------|----------|

## Emballage

|                             |               |
|-----------------------------|---------------|
| Emballage Niveau 1 Unités   | box 1 pièce   |
| Emballage Niveau 1 EAN      | 4016779066778 |
| Emballage Niveau 1 Longueur | 256 mm        |
| Emballage Niveau 1 Hauteur  | 106 mm        |
| Emballage Niveau 1 Largeur  | 125 mm        |
| Emballage Niveau 1 Poids    | 0.718 kg      |

## Technique

|                                     |          |
|-------------------------------------|----------|
| Compatible Bus Systems              | KNX (TP) |
| Indice de protection                | IP20     |
| Type de montage                     | DIN-Rail |
| Width in Number of Modular Spacings | 12       |

## Certificats et Déclarations (Numéro de document)

|  |                 |
|--|-----------------|
| CB Certificate                         | 9AKK107991A3224 |
| Fiche produit, informations techniques | 2CDC505187D0211 |
| Déclaration de Conformité - CE         | 2CDK505259D2701 |
| Instructions et manuels                | 2CDG941213P0001 |
| Informations RoHS                      | 2CDK505259D2701 |

## Environnement

|             |                                   |
|-------------|-----------------------------------|
| Statut RoHS | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Classifications

|  |  |
|--|--|
| ETIM 7                                   | EC001097 - Switch actuator for bus system                  |
| ETIM 8                                   | EC001097 - Switch actuator for bus system                  |
| eClass                                   | V11.0 : 27143125   |
| Catégorie DEEE                           | 5. Small Equipment (No External Dimension More Than 50 cm) |
| UNSPSC                                   | 31251516   |
| Code de catégorie granulaire IDEA (IGCC) | 3268 >> Switch actuator                                    |

## Catégories

Produits basse tension → Home and Building Automation → KNX → Standard Outputs → Switch Actuators 6 A

